NSK Bearing Part Number

NSK bearing part number system

EXAMPLE: 77206M1AC4ES41

77 - Two shields
206 - Basic number
M - Medium fit AFBMA class 0.
1 - ABEC-1 tolerance
AC4 - Andok C, 1/2 full
ES41 - Stabilized heat treatment

EXAMPLE: 6206 DDUYL3BT3ES17

6206 - Basic number. DDU - Two rubber contact seals
Y - Pressed brass retainer
L - Loose fit, AFBMA Class 3
3 - ABEC-3 tolerance
BT3 - Beacon 325, 3/8 full
ES17 - Special cleaning

Part number system:

Prefix	Suffix	Definition
·	+AH	WITHDRAWAL OR
		REMOVAL SLEEVE.
	+H	ADAPTER SLEEVE.
·	+HJ	STABILIZING RING/ CYLINDRICAL ROLLER BEARINGS.
	+K	OUTER RING SPACER, TAPERED ROLLER BEARINGS.
·	+KL	INNER AND OUTER RING SPACER, TAPERED ROLLER BEARINGS.
·	+L	INNER RING SPACER, TAPERED ROLLER BEARINGS.
·	-008	BORE SIZE, 1/2 INCH DIAMETER.
·	-010	BORE SIZE, 5/8 INCH DIAMETER.
·	-100	BORE SIZE, 1 INCH DIAMETER.
·	-107	BORE SIZE, 1-7/16 INCH DIAMETER.
·	-12	BORE SIZE, 3/4 INCH DIAMETER.
·	-13M	BORE SIZE, 13 MM DIAMETER.

14	BORE SIZE, 7/8 INCH DIAMETER.
625	BORE SIZE, 0.6250 INCH DIAMETER.
8	BORE SIZE, 1/2 INCH DIAMETER.
. 1	1/8 FULL.
. 2	1/4 FULL.
. 3	3/8 FULL.
. 4	1/2 FULL.
. 5	5/8 FULL.
. 6	3/4 FULL.
. 7	7/8 FULL.
. 8	100 PERCENT FULL
. 9	DIP.
. А	INTERNAL REDESIGN.
. А	30 DEGREE CONTACT
	ANGLE, ANGULAR CONTACT BALL BEARINGS.
. AB	ANDOK B.
. AC	ANDOK C.
. AE	AEROSHELL 15.
. AE3	ABEC-3 TOLERANCE.
. AE5	ABEC-5 TOLERANCE.
. AF	AEROSHELL 17.
. AK	ANDOK 260.
. AN	ANDEROL L-423 OIL.
. AR	AEROSHELL 5.
. AS	AEROSHELL 7.
. АТ	AEROSHELL 16.
. AW	AEROSHELL 22.
. AX	AEROSHELL 6.
. В	INTERNAL REDESIGN.
. В	40 DEGREE CONTACT ANGLE, ANGULAR CONTACT BALL BEARINGS.
. BS	X8388A (BATCO) .
. ВТ	BEACON 325.
. С	INTERNAL REDESIGN.
. С	15 DEGREE CONTACT ANGLE, ANGULAR
_	CONTACT BALL BEARINGS.
. C2	TIGHT FIT, AFBMA CLASS 2.
. С3	LOOSE FIT, AFEMA CLASS 3.
. C4	EXTRA LOOSE FIT, AFBMA CLASS 4.
. CA	SPHERICAL ROLLER BEARING.

2/10

	cc	STANDARD, NON- INTERCHANGEABLE FIT, CYLINDRICAL ROLLER BEARINGS.
•	CC2	LESS THAN STANDARD NON-INTERCHANGEABLE FIT, CYLINDRICAL BEARINGS.
	CC4	GREATER THAN CC3 FIT, CYLINDRICAL ROLLER BEARINGS.
•	ccs	GREATER THAN CC FIT, CYLINDRICAL ROLLER BEARINGS.
•	CD	SPHERICAL ROLLER BEARING.
	CE	ELECTRIC MOTOR QUALITY BEARING AND FIT.
_	СН	CHEVRON OHT.
	CHS	WATER PUMP BEARING WITH SLINGER RING.
	СМ	ELECTRIC MOTOR QUALITY BEARING AND FIT.
	СТ	ELECTRIC MOTOR QUALITY BEARING AND FIT.
	D	STEEP CONTACT ANGLE, TAPERED ROLLER BEARING.
	DA	DOW CORNING DC99 - NO. 2.
•	DB	SUPERNAL GREASE NO. 72832.
	DB	DOW CORNING FS3451 - NO. 2.
	DB	DUPLEX PAIR, BACK-TO- BACK MOUNTING.
	DDU	TWO RUBBER CONTACT SEALS.
	DE	DC41.
	DF	DC44.
	DH	DOW CORNING 510.
	DH	WATER PUMP BEARING, DULITED AND HANED PARTS.
•	DP	DUPLEX PAIR, FACE-TO- FACE MOUNTING.
	DS	DC FS 1291.
	DT	DC33.
	DT	DUPLEX PAIR, TANDEM MOUNTING.
	DU	SINGLE RUBBER CONTACT SEAL.
•	DV	DC FS 1292.

	E	BEARING WITH SLOT OR KEYWAY.
	E100	SPECIAL BEARINGS (MIL- B-17931C) .
	E101	GREASE QUANTITY AND TEFLON SEAL ELEMENT, SPECIAL.
	E4	OUTER RING RELUBRICATION FEATURE, SPHERICAL BEARINGS.
	ES11	SPECIAL GREASE VOLUME.
	ES12	SPECIAL CARTON MARKING.
	ES13	SPECIAL CORNER RADIUS.
•	ES15	SPECIAL END PLAY.
•	ES16	SPECIAL PROCESSING.
•	ES17	SPECIAL CLEANING.
•	ES18	RADIAL PLAY LIMITS SPECIAL.
•	ES19	SPECIAL CLEANING, LUBRICATION.
•	ES20	RADIAL PLAY, GAGING LOADS, SPECIAL.
	ES21	HEAT STAB, FOR 325°F OPERATION.
	ES22	XT RADIAL PLAY, SPECIAL.
	ES24	(MIL-B-17931A) , AMENDMENT 2, LOW NOISE LEVEL.
	ES25	HIGH-SPEED TEST.
•	ES26	DULITE PROCESSED.
•	ES27	END PLAY AND TILT LIMITS, SPECIAL.
•	ES28	DULITE PROCESSED.
•	ES29	SPECIAL SHIELD MARKING.
	ES3	100 PERCENT SPEED TEST, LOW NOISE LEVEL.
•	ES30	QUALITY AUDIT, SPECIAL.
•	ES31	TORQUE LIMITS, SPECIAL.
•	ES32	SPECIAL INSPECTION.
•	ES33	LOW NOISE LEVEL.
	ES34	ULTRASONIC CLEANING.
	ES35	FLUSHNESS TOLERANCE SPECIAL.
	ES36	SPECIAL IDENTIFICATION.
	ES37	DULITE SHIELD.
	ES38	SPECIAL END PLAY.
	ES39	ELECTRONIC NOISE TESTING.
	ES40	HEAT STABILIZED, SPECIAL.

E	S41 ST	ABILIZATION FOR 375
	•	DEG F OPERATION.
. Е	S42	'HS 2" MARKING ON OUTER.
. Е	S43	GREASE CONTROL, SPECIAL.
. Е	\$44 RI	EDUCED INSPECTION LIMITS.
. Е	S45 L	APPED INNER FACE.
. Е	S46	OVERSIZE O.D. ' S.
. Е	\$47 SP	ECIAL FOR RAILROAD APPLICATION.
. Е	S48 SPE	CIAL O.D. TOLERANCE.
. Е	S49 SH	IELD IDENTIFICATION, SPECIAL.
. Е	S50 REV	VORK IDENTIFICATION.
. Е	001	PECIAL TOLERANCES.
. Е	\$52 SO	LVENT CLEAN PARTS , SPECIAL .
. Е	S53 SF	PECIAL PROCESSING.
. Е	\$54 SP	ECIAL FOR RAILROAD APPLICATIONS.
. Е	S55	SPECIAL 77R6. /
. Е		RADIAL LOOSENESS CHECK ,_ SPECIAL .
. Е	S57 SF	PECIAL O.D. CORNER.
. Е	\$58 HIG	H POINT MARKING ON INNER RING.
. Е	S59	O.D. CODING.
. Е	:S6 (CERTIFIED QUALITY CONTROL.
		SPECIAL GREASING.
. Е	S61	ES-41 AND SPECIAL GREASING.
. Е	S62	SHIELD OR SEAL SSEMBLY, SPECIAL.
. Е	S63	SPECIAL 7038.
. Е	S65	SPECIAL MARKING INSTRUCTIONS.
. Е		ECIAL IDENTIFICATION.
. Е	S67 SI	PECIAL GREASE AND QUANTITY.
. Е	S68	SPECIAL GREASE QUANTITY.
. Е		SPECIAL PROCESS, SPECIAL CARTON MARKING.
. Е	S70	SPECIAL MARKING.
. Е	S71	SPECIAL WIDTH TOLERANCE.
. Е	\$72 SF	PECIAL LUBRICATION.

. ES73	SPECIAL PROCESSING.
. ES74	SPECIAL RING MARKING.
. ES75	BEARINGS SERIAL NUMBERED.
. ES82	RELUBE TYPE SHIELDS.
. ES83	ELECTRO-GALVANIZING .
. ES84	SPEC, INTERNAL CLEARANCE AND SPECIAL GREASE QUANTITY.
. ES85	SPECIAL GREASE QUANTITY.
. ES9	(MIL-B-17931A) , AMENDMENT 1, LOW NOISE LEVEL.
. ESI	HAND SPIN TEST, LOW TORQUE.
. ESS	SHIELD CLEARANCE 0.003 INCH, SPEC, TOLERANCE.
. ESS	LOW NOISE LEVEL.
. F	SINGLE SHIELD, DOUBLE- ROW BALL BEARINGS.
. FF	TWO SHIELDS, DOUBLE- ROW BALL BEARINGS.
. FM	FISKE LUBRIPLATE - MULTI- LUBE A.
. FT	FISKE LUBRIPLATE 210.
. G	SNAP RING ON BEARING.
. GNR	SNAP RING GROOVE ON BEARING, NO SNAP RING.
. GS	SNAP RING ON SAME SIDE OF BEARING AS SHIELD.
. HP	HUMBLE OIL UNIVIS P38.
. HX	HUMBLE OIL UNIREX NO. 2.
. J	PRESSED STEEL RETAINER, TWO PIECE RIBBON TYPE.
. К	TAPERED BORE BEARING 1:12.
. К30	TAPERED BORE BEARING 1:30.
. КН	KEYSTONE 89H.
. KY	DUPONT, KRYTOX 240AC.
. LU	LUBRIKO M24.
. М	MACHINED BRONZE RETAINER.
. М	MEDIUM FIT, AFBMA CLASS 0.
. MT	MOBIL-TEMP £1 SOCONY VACUUM.
. N	SNAP RING GROOVE IN OUTER RING.

. NF	NON-FLUID OIL CP. F924.
. NG	NON-FLUID OIL CO. G-60.
. NR	NOX - RUST 509.
. NR	SNAP RING IN OUTER
	RING.
. NS	NON-FLUID OIL CO. S-59.
. NW	NON-FLUID OIL CO. W-56.
. OS2	WATER PUMP BEARING, SHAFT 0.002 INCH OVERSIZE.
. OS3	WATER PUMP BEARING, SHAFT 0.003 INCH OVERSIZE.
. PE	PETROLATUM
. RR	O.D. RIDING TRASH GUARD RUBBER CONTACT SEALS.
. RS	FACE RIDING RUBBER CONTACT SALES.
. RY	RYKON 12.
. SA	SHELL ALVANIA \$2
. SB	SHELL XSG6409.
. SC	SHELL CYPRINA £3.
. SD	SHELL DARINA J2.
. SE	SHELL DARINA EP.
. SF	SHELL DARINA FL.
. SG	STANDARD GREASE CODE.
. SL	SHELL ALVANIA 13.
. SO	STANOIL 15.
. SP	SHELL ALVANIA \$2 EP. SOUTHWEST GREASE AND
. SW	OIL CO., CODE 5682.
. SX	SHELL DARINA AX.
. т	FACE RIDING TRASH GUARD RUBBER CONTACT SEAL.
. т	TIGHT FIT, AFBMA CLASS 2.
. тв	TEXACO PREMIUM BRB.
. TC	TEXAS CAPELLA B.
. TE	TEXAS EP 2324 HI-TEMP.
. тн	TEXAS 1999 HI-TEMP.
. TL	ASHLAND OIL TECTYL 900.
. тм	TEMPLUBE 124.
. TR	TEXAS REGAL STARFAK AFB-2 .
. тт	TWO FACE RIDING TRASH GUARD RUBBER CONTACT SEALS.
. TU	TEXAS 1996 UNI-TEMP 500.
. TX	TEXAS 1692.

7 / 10

•	UC	SUPERMIL GREASE NO. 31052.
	UF	ASU 40.
_	UN	UNOBA JL UNION OIL.
_	US	ASU 06752 (AMERICAN OIL)
-		
	UT	ASU 100.
	V	LABYRINTH RUBBER SEAL .
	VA	CHEVRON BRB2
	VS	CHEVRON SRI
•	W	TWO LABYRINTH RUBBER SEALS.
•	W	PRESSED STEEL RETAINER, ONE PIECE TYPE.
	WN	WINDSOR L245X
	X	REDESIGNED BOUNDARY DIMENSION OF LESS THAN + 1 MM.
•	XL	EXTRA LOOSE FIT, AFBMA CLASS 3.
-	ХТ	EXTRA TIGHT FIT, LESS THAN AFBMA CLASS 2.
•	Υ	PRESSED BRASS RETAINER, TWO PIECE, RIBBON TYPE.
	Z	SINGLE SHIELD.
-	ZZ	GREASE SPE CIS PART OF ES NUMBER.
	ZZ	TWO SHIELDS.
7		SINGLE SHIELD.
77		TWO SHIELDS.
8		FELT SEAL.
87		ONE FELT SEAL, ONE SHIELD.
88		TWO FELT SEALS.
89	•	ONE FELT SEAL, ONE TEFLON SEAL.
9		TEFLON SEALS.
99		TWO TEFLON SEALS.
Н	•	HEAVY SERIES CUP OR CONE, TAPERED ROLLER BEARINGS.
НН	•	EXTRA HEAVY SERIES CUP OR CONE, TAPERED ROLLER BEARINGS.
НМ		MEDIUM-HEAVY SERIES CUP OR, CONE , TAPERED ROLLER BEARINGS.
L	·	LIGHT SERIES CUP OR CONE, TAPERED ROLLER BEARINGS.

LL		EXTRA LIGHT SERIES CUP OR CONE, TAPERED
LM		ROLLER BEARINGS. MEDIUM-LIGHT SERIES
		CUP OR CONE, TAPERED ROLLER BEARINGS.
M	•	MAX-TYPE, FILLING SLOT BALL BEARINGS.
M		MEDIUM SERIES CUP OR CONE, TAPERED ROLLER BEARINGS.
MS	•	SHIELD AND LOADING SLOT ON SAME SIDE, BALL BEARINGS.
N		CYLINDRICAL BEARING, DOUBLE FLANGED INNER, OPEN OUTER.
NF		CYLINDRICAL BEARING, DOUBLE FLANGED INNER, SINGLE FLANGED OUTER.
NH		CYLINDRICAL BEARING, TWO-PIECE INNER, DOUBLE FLANGED OUTER.
NJ		CYLINDRICAL BEARING, SINGLE, FLANGED INNER, DOUBLE FLANGED OUTER.
NN		CYLINDRICAL BEARING, DOUBLE-ROW, FLANGED INNER, OPEN OUTER.
NU		CYLINDRICAL BEARING, OPEN INNER, DOUBLE FLANGED OUTER.
R	•	INCH DIMENSION SERIES BALL BEARINGS.
RA		POWER TRANSMISSION BALL BEARINGS, PRELUBRICATED.
RAG		POWER TRANSMISSION BALL BEARINGS, RELUBRICATEABLE.
S		CARTRIDGE BEARING SERIES.
SB		POWER TRANSMISSION BEARING, WIDE INNER, PRELUBRICATED.
SBG		POWER TRANSMISSION BEARING, WIDE INNER, RELUBRICATEABLE.
SE		ECCENTRIC LOCKING COLLAR FOR POWER TRANSMISSION.
SF	•	FOUR-BOLT FLANGE UNIT, STANDARD, RELUBRICATEABLE.
SFC		FOUR-BOLT FLANGE UNIT,

1	RA UNIT, PRELUBRICATED.
SFT	. TWO-BOLT FLANGE UNIT, STANDARD, RELUBRICATEABLE.
SFTC	. TWO-BOLT FLANGE UNIT, RA UNIT, PRELUBRICATED.
SP	. STANDARD HEIGHT PILLOW BLOCK, RELUBRICATEABLE.
SPC	. STANDARD HEIGHT PILLOW BLOCK, RA UNIT, PRELUBRICATED.
SPEC	. REVISED HEIGHT PILLOW BLOCK, RA UNIT, PRELUBRICATED.
SPH	. REVISED HEIGHT PILLOW BLOCK, RELUBRICATEABLE.
STU	. TAKE-UP UNIT BLOCK, RELUBRICATEABLE.
STUC	. TAKE-UP UNIT BLOCK, RA UNIT, PRELUBRICATED.
wc	. FELT SEAL SERIES BEARINGS, WIDE OUTER RING.
X	. SPECIAL BEARING SERIES.